KC-BRAINware-5

Hardware Platform with 5 Instances of
Kramer BRAINware

| HDMI | Ethernet - RJ-45

KC‑BRAINware‑5 is a hardware platform with 5 instances of Kramer BRAINware software already installed on the device. KC‑BRAINware‑5 is designed to maximize the features and benefits of Kramer BRAINware for controlling up to 5 standard spaces (e.g. a standard space could include a scaler, monitor, lighting system, touch panel and keypad).

Kramer BRAINware is an enterprise‑class, revolutionary, user‑friendly, software application that enables you to execute all your room control actions straight from a computer without installing a physical Brain between the user interface and the controlled devices. Using the power of Kramer Control cloud–based control & space management platform, Kramer BRAINware enables you to operate multiple devices over Ethernet such as scalers, video displays, audio amplifiers, Blu‑ray players, sensors, screens, shades, door locks, and lights.

Designing a system was never easier, with Kramer Control's programming free, intuitive drag & drop Builder. Install, configure and modify your control system without any prior knowledge in programming

FEATURES

Simplified AV Installation - Control up to 5 rooms without installing a physical Brain

Scalable to Your Installation - Supports controlling up to 5 standard spaces

Format Conversion - Use Kramer FC family of control format converters to enable controlling almost any device

Fully Customizable UI - Using Kramer Control, easily personalize your control interface any way you like

Space Controller - Controls any AV device with its corresponding logic

No Programming Required - Install and start using the platform in minutes with no need for programming

TECHNICAL SPECIFICATIONS

Ports	4 USB: On USB 3.0 connectors
	1 LAN: On an RJ−45 connector
Outputs	1 HDMI: On a female HDMI connector
	1 DisplayPort: On a female Mini DisplayPort connector
	Note: Does not support graphic output to both the HDMI and Mini Display Port simultaneously
	1 Unbalanced Audio: On a 3.5mm mini jack for headphones/speakers
General	Processor: 4th generation Intel® Dual core 1.4GHz
	Main Memory: 4GB, high speed
	Storage: 32GB, solid−state drive
	LAN: Gigabit LAN
Audio	Analog or embedded HDMI, S/PDIF Realtek ALC269 :
Power	Source: 19V DC
	Consumption: 700mA

ACCESSORIES:

Accessories	Included: Power cord, VESA mounting bracket
Environmental Conditions	Operating Temperature 0° to +40°C (32° to 104°F)
	Storage Temperature −40° to +70°C (−40° to 158°F)
	Humidity 10% to 90%, RHL non−condensing

HDMI OUT

HDMI   DP   Eth   USB   USB

OR

Display   Display   Keyboard

Wireless
Router

Mouse