



kramer

KW-14T

Wireless HD Transmitter

| HDMI | HDCP Compliant



The KW-14T is a high-definition, wireless, HDMI transmitter for indoor use. Up to four KW-14R receivers can receive from one KW-14T transmitter and up to three KW-14T transmitters can be paired with one KW-14R receiver. The KW-14T and KW-14R pair comes pre-associated

FEATURES

Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel), Deep Color up to 12-bit

Secure Link - Uses AES-128 bit encryption

Connection Capacity - Up to four receivers can receive from one transmitter simultaneously; up to three transmitters associated with one receiver at any given time

Transmission Range - Up to 30m (100ft) including through walls and furniture

Automatic Frequency Selection - Selects the most suitable frequencies to prevent RF interference

Auto EDID Adjustment - To allow multi-screen support

IR Remote Control - Enables the OSD menu to be displayed on the output display

OSD (On Screen Display) - For simplified setup and configuration

HDCP Compliant - HDCP sources are supported only when all connected displays support HDCP

Zero Latency

Automatic Sleep Mode - After three minutes when no input or link is detected



kramer

TECHNICAL SPECIFICATIONS

INPUT:	1 HDMI connector
OUTPUT:	1 IR on a 3.5mm mini jack, internal antenna
VIDEO RESOLUTION:	Up to 1080p @60Hz; 8, 10, or 12-bit color depth and VESA up to 1920 x 1080 @60Hz
FORMATS:	RGB and YCbCr digital video
MAXIMUM DATA RATE:	6.75Gbps (2.25Gbps per channel)
MAXIMUM PIXEL CLOCK:	148.5MHz
AUDIO FORMATS:	PCM, Dolby Digital 2/0, Dolby Digital 2/0 Surround, Dolby Digital 5.1, Dolby Digital Surround EX, DTS 2-channel, DTS Digital Surround 5.1, DTS 96/24
AUDIO RATE:	Digital audio from the HDMI input up to 6Mbps
RF COMMUNICATION FREQUENCY:	5.19 to 5.795GHz (In Israel operation is limited to 5.15 to 5.35GHz)
TRANSMISSION POWER:	<18dBm conducted (KW-14T), <12dBm per channel conducted (KW-14R)
RECEIVING SENSITIVITY:	-75dBm (KW-14T), -65dBm (KW-14R)
SYSTEM LATENCY:	<1ms
STANDARDS:	HDMI with Deep Color, x.v.Color™, 3D; HDCP 2.0—works with sources that support HDCP repeater mode, DVI 1.0
UNOBSTRUCTED TRANSMISSION RANGE:	30m (100ft)
POWER CONSUMPTION:	5V DC, 1A
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
COOLING:	Convection, vented
ENCLOSURE TYPE:	Plastic
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHS and WEEE
VIBRATION:	ISTA 1A in carton (International Safe Transit Association)
COMPLIANCE STANDARDS:	CE, c-UL, UL
EMMISSION STANDARDS:	CE, C-tick, FCC Class B, ICES, VCCI, KC
INCLUDED ACCESSORIES:	Power supply 5V, 2 HDMI cables 0.9m (2.95ft) PN 2518-0101003, 1 IR emitter cable PN 3300-500135

Product Dimensions 8.00cm x 10.20cm x 3.60cm (3.15" x 4.02" x 1.42") W, D, H

Product Weight 0.1kg (0.3lbs) approx

Shipping Dimensions 23.20cm x 12.00cm x 8.90cm (9.13" x 4.72" x 3.50") W, D, H

Shipping Weight 0.5kg (1.2lbs) approx

