



# kramer

## TBUS-201xl

Pop-Up Table Mount Multi-Connection Solution

| VGA/UXGA - 15-pin HD | HDMI | Ethernet - RJ-45



Kramer's TBUS-201xl provides an extremely simple, affordable and elegant single-push pop-up multi-connection boardroom solution. By pressing down gently on the lid, the unit opens and closes pneumatically. TBUS-201xl is fast and easy to install and flexible to configure. It customizes to your own needs and is intuitive to operate. The power socket module is not included. Purchase the country-specific module separately

### FEATURES

**Pneumatic Lift** - Easy opening & closing by pressing down gently on the cover. When not in use, it lowers flush with the table

**Power Input** - Universal, USA, European and many other worldwide power sockets available

**4 Fixed Inputs** - 15-pin HD, HDMI, 3.5mm & Ethernet

**Elegant and Rugged Rectangular Design** - The sturdy and attractive anodized aluminum enclosure provides maximum connectivity in the smallest possible footprint, and at the same time is cost effective and easy to install

**Installation** - Requires tools and expertise to cut a 133mm x 120mm (5.2" x 4.7") rectangular hole in the surface of the furniture. Maximum table thickness is 7.6cm (3")

**Note** - The power socket module is not included. Purchase the country-specific module separately



# kramer

## TECHNICAL SPECIFICATIONS

---

PORTS:	1 HDMI connector, 1 Ethernet RJ-45 connector, 1 15-pin HD connector, 1 3.5mm mini jack
POWER SOCKET ASSEMBLIES:	USA Universal 100–240V AC, 50/60Hz, 5A per outlet; 100–220V AC, 50/60Hz, 5A per outlet; Germany and EU 100–240V AC, 50/60Hz, 5A per outlet; Belgium and France 100–240V AC, 50/60Hz, 5A per outlet; Italy 100–240V AC, 50/60Hz, 5A per outlet; Australia 100–240V AC, 50/60Hz, 5A per outlet; Israel 220V AC, 50/60Hz, 5A per outlet; South Africa 220V AC, 50/60Hz, 5A per outlet; Switzerland 220V AC, 50/60Hz, 5A per outlet; UK 220V AC, 50/60Hz, 5A per outlet; Brazil 220V AC, 50/60Hz, 5A per outlet
OPERATING TEMPERATURE RANGE:	+5° to +45°C (41° to 113°F)
OPERATING HUMIDITY RANGE:	10 to 90% RHL, non-condensing
STORAGE TEMPERATURE RANGE:	-20° to +70°C (-4° to 158°F)
STORAGE HUMIDITY RANGE:	5 to 95% RHL, non-condensing
INCLUDED ACCESSORIES:	Cardboard template
OPTIONS:	Power socket kits, power cord
Product Dimensions	15.20cm x 13.93cm x 17.38cm (5.98" x 5.48" x 6.84" ) W, D, H
Product Weight	0.9kg (2.0lbs) approx
Shipping Dimensions	21.50cm x 19.00cm x 20.70cm (8.46" x 7.48" x 8.15" ) W, D, H
Shipping Weight	1.5kg (3.3lbs) approx



## CONFIGURATIONS

TBUS-201XL(B)	Enclosure - Black Sand Blasted Anodized Aluminum Top
TBUS-201XL(BC)	Enclosure - Silver Sand Blasted Anodized Aluminum Top

