



# kramer

## C-SM/SM

s-Video Cable

---



Kramer's C-SM/SM is a high performance s-Video (Y/C) cable with molded 4-pin mini DIN connectors at each end. Luminance and chrominance signals are carried on separate internal coaxes for superior quality over composite video

### FEATURES

---

**Quality Construction** - Passes luminance (Y) and chrominance (C) signals over a high-quality 26AWG dual coax cable terminated with 4-pin mini DIN connectors

**High-Quality Connectors** - Gold-plated connectors for corrosion resistance and best possible connection

**Cable Specs** - For detailed cable specs, see Kramer BC-2X

**Varied Selection of Lengths** - Available in versions of 0.9 to 30.5m (3 to 100ft)



# kramer

## TECHNICAL SPECIFICATIONS

---

COAX	Coax Center Conductor: 26 AWG 7/34 tinned copper Dielectric: Foam polyethylene Shield: (A) 90% spiral 38 AWG tinned copper. (B) Aluminum Mylar foil 25% overlap rate
CONSTRUCTION	Drain Wire: 24 AWG 7/32 tinned copper Coax Jacket Colors: Yellow, white Outer Jacket: PVC Outer Jacket Color: Dark gray with white lettering
DIAMETERS	Center Conductor: 0.474mm (0.018in) Dielectric: 1.95mm (0.17in) Individual Coax: 2.6mm (0.102in) Outside Diameter: 6.2mm (0.244in)
ELECTRICAL	Impedance: 75 $\Omega$ DC Resistance: 148 $\Omega$ /km (45 $\Omega$ /1000ft) Capacitance: 53.1pF/m (17.3pF/ft) Velocity of Propagation: 76% Temperature: -20° to 75°C (-4° to 167°F) Attenuation (dB/100 ft.): -0.5dB @1MHz -1.2dB @5MHz -1.8dB @10MHz -4.4dB @50MHz -6.7dB @100MHz
REGULATORY	UL: CL2 CSA: C(UL) CL2



# kramer

## CONFIGURATIONS

---

C-SM/SM-3	4-pin Mini DIN (M) to 4-pin Mini DIN (M) s-Video Cable
-----------	--

---

C-SM/SM-6	4-pin Mini DIN (M) to 4-pin Mini DIN (M) s-Video Cable
-----------	--

---

C-SM/SM-25	4-pin Mini DIN (M) to 4-pin Mini DIN (M) s-Video Cable
------------	--

---

C-SM/SM-75	4-pin Mini DIN (M) to 4-pin Mini DIN (M) s-Video Cable
------------	--

---