

iSpeaker DAC6S
Dante Ceiling Speaker 6.5"





INTRODUCTION

The 6.5-inch coaxial unit has a sensitivity of 95dB and an output power of 60W. It has high sound pressure level output and large dynamic response. Front-out wiring design facilitates system construction. Designed with 8x N42 high-strength magnets to install the grille, it can be installed in a narrow ceiling spaces and suitable for a wide range of applications.

FEATURES

- 1x6.5"+1x1" dome
- Sensitivity of 93dB
- Output power of 60W
- Rated power (8Ω fixed resistance): 60W
- Designed with 8x N42 high-strength magnets, more stable.
- With anti-dropping rope.
- Easy wiring: Front-out wiring cable raceway.
- Suitable for narrow ceiling spaces.
- Supports Dante
- Supports PoE: 802.3af/802.3at/802.3bt

TECHICAL SPEC

Model	iSpeaker DAC6S
Name	Dante Ceiling Speaker 6.5”
Structure	1x6.5"+1x1" dome, coaxial design.
Rated Impedance	8Ω
Rated power	60W
Effective frequency range	75Hz~20KHz
Sensitivity level (1m/1W)	93dB
Sound pressure level	In specified frequency band: 110dB
Net cover material	Metal mesh
Back shell material	Iron
Installation dimension	Total height: 197mm Embedded depth: 176mm Installation thickness: 10-50mm Opening diameter: 270-280mm Speaker outer diameter: 316mm
Port	Dante RJ45 PoE
PoE	802.3af/802.3at/802.3bt
Net Weight	4.87kg
Gross Weight	6.4kg